Episode Book

EPISODE #5516

Wall Anchors: Why Your Holes Keep Failing

PUBLISHED	24 September 2026 at 12:48 UTC
DURATION	24:13
LISTEN	myweirdprompts.com/episode/wall-anchors-failing-holes/
HOSTS	Corn, Herman, Hilbert
SCRIPT MODEL	deepseek-flash
VOICES	chatterbox-regular (chatterbox-local)
PIPELINE	V5.2
BOOK GENERATED	19 October 2026 at 17:37 UTC

SYNOPSIS

Daniel wrote in with a problem every DIYer eventually hits: anchors that won't hold, in walls where drilling a clean hole is nearly impossible. We dig into the actual mechanism of wall plugs — why "nylon anchors expand" is technically true and practically misleading — and why a hole just 1/16" too wide renders a plastic anchor useless. Then we walk through the categories that actually solve compromised holes: zinc self-drilling anchors, sleeve anchors, toggles, and when to stop looking for a better plug and switch fastener categories entirely. If you've ever stood in front of a wall with three failed holes behind you, this one's for you.

TRANSCRIPT



Corn

Here's a question that sounds boring until you've spent twenty minutes on your knees in front of a wall, drill in hand, with three failed holes behind you.



Corn

Daniel wrote in about anchors. Wall anchors. And he's right that it's not a topic that animates most people, but if you're doing it repetitively, it's worth knowing how to do well.



Corn

His situation: hardware stores in Israel are hit and miss for solutions. For drywall, the most commonly sold anchor is a hammer-in type, and he finds them very hard to use. He picked up a zinc alloy screw-in type on AliExpress, and those are complete game changers, though he's never seen them sold locally.



Corn

For concrete he uses regular nylon anchors, sometimes the heavy duty kind. Those two variants cover most situations.



Corn

But here's the edge case, and this is the heart of it. Walls where drilling straight is really difficult because the material changes halfway through, or concrete has hard and soft portions, so you can't get a consistent hole. You choose the perfect bit size, you've got the right anchor that's worked many times before, and it still won't hold. You try another one. Now you've got three anchors that don't fit.



Corn

What he wants is an anchor that truly expands to form a tight grip in those edge case holes where a perfect circular hole is almost impossible.



Corn

And he's skeptical about nylon. He's always heard they expand, that that's their whole thing, but he's yet to see one start a tiny bit loose and then harden into a perfect fit. He doesn't think that's what they do.



Corn

Two specific asks. Without getting into epoxy anchors, are there types optimal for this situation? And if you know you're going to get an imperfect hole and you're counting on a little bit of expansion, do you drill narrower than you normally would?



Herman

There's a lot packed in there.



Corn

There is. Let's start with the part where Daniel is right and everyone who's ever sold him an anchor is wrong.



Herman

The expansion myth.



Corn

Because "nylon anchors expand" is technically true and practically misleading in exactly the way he suspects.



Herman

Let's define the thing first. A wall plug is a hollow sleeve. Nylon, polyethylene, PVC. Typically twenty to fifty millimeters long, with longitudinal slots cut along most of its length. You drive a screw into the bore, the screw threads cut into the inner bore, and the plug body expands radially outward through those slots.



Herman

Radial. Outward from the axis. That's the whole mechanism.



Corn

And bounded.



Herman

And bounded. The plug expands exactly as far as the screw forces it, and no further. Which means the substrate has to push back. The plug needs something with compressive strength on the other side of it to grip against.



Corn

So in soft or crumbly material...




Herman

The plug widens the hole instead of gripping it. The plug expands, the plasterboard around the plug crumbles, the plug widens the hole, and the entire assembly pulls out under the slightest load. That's not a failure of the anchor. That's the anchor doing exactly what it does, into a material that can't hold it.



Corn

So Daniel's intuition is correct. A nylon anchor does not start a tiny bit loose and then harden into a perfect fit.



Herman

It cannot. It has no mechanism to close a gap larger than its expansion range, and it has no mechanism to grip a hole that's already oversized. The expansion range of a typical nylon plug is a couple of millimeters at most.



Corn

Two millimeters. So if your hole is one sixteenth of an inch too wide...



Herman

A hole even one sixteenth of an inch too wide renders the anchor useless. That's the number. Not "degrades performance." Renders it useless.



Corn

Which is a brutal margin for something you're drilling freehand into a wall you can't see inside.



Herman

And that's the thing. Plastic expansion anchors rely on friction-based fit. That's the weakest form of mechanical connection you can make in a porous material like gypsum. Compared to a threaded anchor, they have almost zero tensile strength. Pull-out resistance, basically nothing.



Corn

So the whole premise of "expansion saves a bad hole" is...



Herman

Largely a myth for oversized holes. Expansion helps when the hole is slightly undersized relative to the plug. That's the regime where it works. Once the hole is oversized, expansion is irrelevant, because there's nothing for the expanded plug to press against.



Corn

Hold on. Say that again, because I want to make sure I've got it.



Herman

Expansion is a grip multiplier, not a gap filler. It multiplies contact pressure against a wall that's already there. It doesn't create wall where there isn't any.



Corn

Right. So the plug is a wedge, not a balloon.



Herman

The plug is a wedge, not a balloon. That's exactly it.



Corn

Okay. Now the hammer-in anchors. Why are these so universally hated?



Herman

Because they're designed for a world where everything goes right. They ship as a single plug-and-screw assembly. You drill, you insert, you drive home with a hammer. The screw is permanent. It cannot be unscrewed to remove the fixing later. You can only cut it off.



Corn

So if you get it wrong, you don't get a do-over, you get a wall with a metal stub in it.



Herman

You get a wall with a metal stub in it.



Corn

And the failure mode?



Herman

The most common one is an anchor that spins in place when the screw is inserted. It just rotates. You turn the screwdriver and nothing happens except the anchor spinning in the hole.



Corn

Which means it never generated friction.



Herman

Never generated friction. Usually because the pilot hole was drilled slightly too large, or the drywall is too thin and crumbling. If the anchor doesn't fit snugly before the screw enters, it will never generate the friction required to expand properly.



Corn

So the anchor has to be tight before it's tight.



Herman

The anchor has to be tight before it's tight. It's a self-defeating design for anyone who isn't perfectly consistent with a drill.



Corn

And that's the thing about hammer-in anchors. They assume you drilled the perfect hole. The whole design is built on an assumption that the hardest part of the job already went right.



Herman

Which is why the zinc screw-in anchors feel like a game changer.



Corn

Daniel's AliExpress find.



Herman

Deep, aggressive threads that bite directly into the gypsum. Unlike plastic sleeves, they create a mechanical bond by threading into the wall much like a screw threads into wood. Most of them require no pilot hole at all in standard half-inch drywall.



Corn

No pilot hole.



Herman

You just drive them in.



Corn

Which eliminates the entire failure pattern.



Herman

Entirely. The pilot hole sizing problem is where hammer-in and plastic anchors die. The zinc self-drilling anchor just bypasses it. There's no hole to get wrong.



Corn

And the material itself matters. Zinc versus plastic.



Herman

Zinc gives you a rigid, metal-to-gypsum connection that's far less likely to wobble or pull through. Because the metal does not compress or deform like plastic, it creates a much broader surface area of contact within the wall.



Corn

Broader contact. So it's not just that the thread is better, it's that the whole body is stiffer.



Herman

The whole body is stiffer. Plastic deforms under load. Metal doesn't. That's the difference between a connection that holds and a connection that creeps.



Corn

There was actual testing on this. A Butterfly House ran a nine-anchor test and rated the metal screw-type anchor five stars. Their words: "The metal version of this anchor is fantastic. It's self-drilling, easy to install, removable and reusable."



Herman

Removable and reusable. Which is the other thing. The plastic version of the same design got two stars from the same tester. "I honestly cannot get one of these into the wall without stripping the plus sign. Sometimes the plastic ones shatter."



Corn

Shatter.



Herman

Shatter. So you've got the same nominal design, one in metal and one in plastic, and the plastic one shatters during installation.



Corn

So Daniel's AliExpress find isn't a placebo. It's a better product category. The reason it feels like a game changer is that it is one.



Herman

It is one. And it's worth noting why he can't find them locally. There's no evidence I could find on Israeli-specific anchor availability or brands. His observation that zinc screw-in anchors aren't sold locally couldn't be verified or explained from anything I looked at. It may just be a distribution gap.



Corn

Or a market that hasn't caught up.



Herman

Either way, it's not him imagining the difference.



Corn

One caveat on the zinc anchors, though.



Herman

Over-torquing. They can strip out. Over-torquing can easily strip out the gypsum core, leaving a gaping hole where the threads used to be. Use a manual screwdriver for the final turns.



Corn

So the last quarter turn, put the drill down.



Herman

Put the drill down. That's the whole trick. The zinc anchor will hold beautifully if you don't murder it on installation.



Corn

Okay. So that's the mechanism and the categories. Now the actual question. The edge cases. The wall where the material changes halfway through, or the concrete with hard and soft portions.



Herman

This is where it gets interesting, because Daniel's problem isn't an anchor problem. It's a substrate problem.



Corn

Meaning?



Herman

Meaning the anchor can only be as good as the material around it. If the material is inconsistent, no anchor is going to be consistent.



Corn

So what do you do?



Herman

First thing: if you can't tell whether your substrate is hollow or solid, drill a small test hole first. Hollow brick and core-filled block look identical from the outside. The drill bit tells the truth in thirty seconds.



Corn

Thirty seconds.



Herman

Thirty seconds. And hitting an unexpected cavity halfway through tightening is the most common cause of "the anchor turns when I tighten it" posts on every forum on the internet. People assume the anchor is bad. The anchor is fine. The wall had a void in it.



Corn

So the test hole is the diagnostic.




Herman

The test hole is the diagnostic. You're not drilling to install anything. You're drilling to find out what's back there.



Corn

And once you know what's back there?



Herman

Then you pick the category. And this is the key insight for Daniel's problem. The real fix for a bad hole is a category switch, not a better plug.



Corn

Say more.



Herman

When a hole is compromised, you don't go looking for a magic expanding plug. You move up a plug size, or you relocate the hole fifty millimeters, or you switch to a toggle, a sleeve, or a chemical anchor. You change the category of fastener, not the brand of the same category.



Corn

Because no plug in the same category is going to solve it.



Herman

No plug in the same category is going to solve it.



Corn

So let's go through the categories. Sleeve anchors first.



Herman

Sleeve anchors are the most forgiving mechanical option for irregular or weaker substrates. Tightening the nut compresses the sleeve along its entire length against the concrete or brick wall. The holding force is distributed along the full sleeve length rather than concentrated at a wedge cone.



Corn

Distributed versus concentrated.



Herman

And that's the difference between a sleeve anchor and a wedge anchor. A wedge anchor concentrates all its force at the wedge cone at the bottom. A sleeve anchor spreads it along the whole sleeve.



Corn

So in an irregular substrate...



Herman

The sleeve wins, because even if one section of the hole is weak, the rest of the sleeve is still gripping.



Corn

What about the wedge anchor?




Herman

Strongest in solid concrete. Wedge anchors carry roughly forty to sixty percent more tension and shear capacity than a sleeve anchor of the same diameter. A properly installed three-eighths-inch sleeve anchor in four thousand PSI concrete holds about eighteen hundred pounds in tension. The wedge anchor is more than that.



Corn

But.



Herman

But wedge anchors do not work in hollow block. The anchor will spin in the hole when you try to tighten it. Which is the exact failure Daniel described. Spinning anchor.



Corn

So the wedge anchor is a specialist for perfect concrete, and the sleeve anchor is the generalist for everything else.



Herman

And sleeve anchors work in concrete, block, and brick. Wedge anchors do not work in hollow block.



Corn

What about the hollow wall case? Toggle bolts.



Herman

Toggle bolts are the answer for hollow walls. A toggle distributes its load across a wide footprint behind the wall, typically two to three times the size of the bolt itself. They work in drywall, plaster on lath, hollow concrete block, panel doors.



Corn

And the load rating?



Herman

Rated twenty to thirty-five kilograms, versus two to ten kilograms for a plastic plug. So a toggle bolt is three to four times the capacity of the best plastic plug.



Corn

That's a big jump.



Herman

It's a big jump because the toggle is bearing on a completely different surface. The plastic plug bears on the inside of a small hole in drywall. The toggle bears on the back face of the drywall, spread across a wide metal bar.



Corn

So it's not the anchor getting better. It's the anchor changing what it's gripping.



Herman

Which is why category switch is the answer.



Corn

Okay. Now the question Daniel actually wants answered. Is there an anchor that truly expands to grip an imperfect hole?




Herman

There's no anchor that expands to close an oversized hole. The physics don't allow it. Expansion is bounded by the screw's displacement of the plug material, and a plug can only expand a few millimeters.



Corn

So the dream anchor doesn't exist.



Herman

The dream anchor doesn't exist in the way he's imagining. But there is a real product that gets closer than anything else, and it's designed for exactly his problem.



Corn

Go on.



Herman

Mungo's Quattro Technology. The MQL series. The plug has four distinct expansion zones distributed along its length, each capable of expanding independently to grip the substrate at four separate depths.



Corn

Four separate depths.



Herman

Standard wall plugs have a single expansion zone near the back of the plug. Quattro plugs grip at four points.



Corn

And the reason that matters for Daniel's wall...



Herman

In perforated brick and aerated concrete, the substrate is alternating layers of solid material and voids. A standard single-expansion plug may land entirely in a void. Grip-free. Useless. Quattro Technology distributes the expansion across four zones, virtually guaranteeing that at least two or three zones land in solid substrate material regardless of where the plug sits.



Corn

So it's not expanding more. It's expanding in more places.



Herman

Which is the actual engineering answer to "the material changes halfway through." You can't make one grip point cover a discontinuous wall. So you make four grip points and bet that some of them land on solid material.



Corn

That's clever.



Herman

It's clever. And it's the single best answer to Daniel's problem. The caveat is that it's a Swiss premium product. Mungo. Not a cheap commodity. Availability in Israel is unverified.



Corn

So it may or may not be findable.




Herman

May or may not be findable. But it's the category of thing he's asking for. Multi-zone expansion. Not a magic expanding plug, but a plug that grips in more places.



Corn

Okay. Now his second question. The narrower drill.



Herman

Yes, but only slightly, and it's the standard rule rather than a special trick.



Corn

So it's not a hack for edge cases. It's just the correct way to drill.



Herman

Always use a drill bit that is slightly smaller than the diameter of the anchor's body. The anchor should require a light tap with a hammer to sit flush against the wall. The plug should slide in by hand with light thumb pressure. If it requires hammering, the hole is too small. If it falls in loose, the hole is too large.



Corn

So there's a test.



Herman

There's a test. Thumb pressure. The plug should go in with thumb pressure.



Corn

And the critical rule that most people get wrong?



Herman

Drill size matches plug size, not screw size. A yellow plug needs a five millimeter drill regardless of whether you're using a number six or a number eight screw. The most common DIY mistake is drilling a hole sized for the screw. The plug is then too loose to grip.



Corn

So the plug and the screw are different systems.



Herman

Different systems. The drill matches the plug. The screw matches the plug. The drill does not match the screw.



Corn

And the counterintuitive warning?



Herman

Drilling too narrow is also a failure pattern. If the plug cracks or splits during installation, the hole was too small, or there was impact from a hammer instead of push-in. So the margin is narrow. Slightly undersized is right, but not so tight the plug splits.



Corn

So you're threading a needle.



Herman

You're threading a needle. Which is why the self-drilling zinc anchors feel so liberating. They don't require you to thread the needle.



Corn

Right. The zinc anchor removes the drill-size decision entirely.



Herman

Removes it entirely. There's no hole to size wrong.



Corn

Let's do the color system, because it's useful and Daniel will want it.



Herman

It originated with UK Rawlplug. Yellow is roughly five millimeter plug, five millimeter drill, number six to eight screws. Red is six millimeter, six millimeter drill, number eight to ten. Brown is seven millimeter, seven millimeter drill, number ten to fourteen. Blue is ten millimeter, ten millimeter drill, number fourteen to eighteen.



Corn

And the load ratings?



Herman

In solid brick or concrete: Yellow five to ten kilograms. Red fifteen to twenty-five. Brown thirty to fifty. Blue sixty to one hundred. And the Mungo MQL-ST Quattro in ten millimeter is over a hundred kilograms.



Corn

Plasterboard anchors?



Herman

Self-drilling plug, five to ten kilograms. Spring toggle, fifteen to thirty. Molly bolt, ten to twenty-five. Toggle bolt, twenty to thirty-five.



Corn

So the toggle bolt more than triples the self-drilling plug.



Herman

More than triples it. Which is why you don't hang a shelf on a self-drilling plug if you can reach behind the wall.



Corn

Now the spaghetti trick.



Herman

The spaghetti trick. Matchsticks or toothpicks stuffed into an oversized hole. It has its devotees. It's a hack, not a fix. For any load over five kilograms, do the job properly.



Corn

Which is exactly Daniel's three-anchors-that-don't-fit scenario.



Herman

Exactly that scenario. If you're on your third anchor and you're reaching for matchsticks, you've already lost. The answer is a category switch.



Corn

Which brings up the weight-rating myth.



Herman

Manufacturer weight ratings are often based on shear strength, which assumes the load is pulling straight down against the wall. Always divide the manufacturer's weight rating by four for a realistic safety margin.



Corn

Divide by four.



Herman

And if the load is dynamic, if it's something that moves or vibrates, reduce capacity by another fifty to seventy percent.



Corn

So a fifty kilogram brown plug is really a twelve kilogram plug, and if it's a moving load, six.




Herman

Six. Which is why a shelf that holds a stack of books is not the same as a shelf that holds a running appliance.



Corn

And the single biggest cause of failure?



Herman

The single biggest cause of wall plug failure customers experience is using a standard nylon plug in plasterboard. Plasterboard has no compressive strength to grip the plug's expansion force. The plug simply widens the hole and falls out.



Corn

Which is the whole thesis. Expansion needs something to push against.



Herman

In plasterboard, there's nothing.



Corn

Daniel's been right the whole time.



Herman

Daniel's been right the whole time. Nylon anchors don't harden into a perfect fit. The whole premise of expansion saving a bad hole is largely a myth for oversized holes.



Corn

The fix for a bad hole is a category switch, not a better plug.



Herman

Category switch, not a better plug.



Hilbert

It's not a five millimeter drill for a yellow plug.



Corn

Sorry?



Hilbert

Yellow plug. The box says five millimeter. The hole you actually want is four point eight. Five millimeter bit, brand new, drills a five point one hole. Old bit, four point seven. That's the whole problem.



Corn

Huh.



Hilbert

I worked a summer at a hardware store with an anchor aisle. Whole wall of little plastic bags and blister packs. I was the guy who had to explain which one you needed.



Herman

The hammer-in drywall anchors?



Hilbert

I had a grudge against those. Watched dozens of people buy them, come back the next day with a broken one, buy the same thing again. Same guy, three weeks in a row, same anchor.



Corn

What did you tell them?



Hilbert

I told them to buy the zinc ones. Half of them didn't believe me because the zinc ones cost more. The other half came back and bought the zinc ones.



Herman

Daniel's instinct about the zinc anchors is right.



Hilbert

The reason they feel like a game changer isn't just that they hold better. It's that they eliminate the pilot-hole sizing problem entirely. The guys who could never get the drill size right, the self-drilling zinc anchors just bypassed that whole failure pattern.



Corn

The anchor doesn't have to be perfect. It just has to not require you to be perfect.



Hilbert

And we had a secret box of Mungo Quattro plugs behind the counter. Expensive. The contractor regulars asked for them by name.



Herman

By name.



Hilbert

By name. The guys who hung heavy things in old buildings swore by them. I watched one of them buy a single Quattro plug, install it in a crumbling old wall, hang a heavy mirror on it, and come back a week later to buy ten more. He told me, "This is the only thing that works when the wall is half brick and half nothing."



Corn

Half brick and half nothing.



Hilbert

That's the wall Daniel's describing.



Corn

That's exactly the wall Daniel's describing.



Hilbert

Anyway. I've got to go. Something outside needs moving before it gets dark.



Corn

Okay.



Herman

The multi-zone expansion is the answer, and the reason it works is that it doesn't try to make one grip point cover a discontinuous wall.



Corn

It makes four grip points and bets that some of them land on solid material.



Herman

Some of them land on solid material. And the wall that's half brick and half nothing is exactly the wall that needs four grip points instead of one.



Corn

If you take one thing from this, it's that expansion is a grip multiplier, not a gap filler. The plug is a wedge, not a balloon.



Herman

A wedge, not a balloon. And a wedge needs something to push against. Which is why the fix for a bad hole is never a better plug. It's a different category of fastener.



Corn

The research found no evidence of any anchor that truly expands to close an oversized hole short of chemical anchors. The physics don't allow it.



Herman

The closest engineered answer is Mungo's Quattro multi-zone expansion plug, but availability in Israel is unverified.



Corn

Daniel's observation that zinc screw-in anchors aren't sold locally couldn't be verified or explained from available sources. It may just be a distribution gap.



Herman

A distribution gap. Which means if you're in Jerusalem and you want zinc anchors, AliExpress may be the only option.



Corn

If you enjoyed this episode, please leave a review on your podcast platform of choice. It helps other listeners find the show.



Herman

Thanks to our producer, Hilbert Flumingtop.



Corn

This has been My Weird Prompts.



Herman

The human-AI collaboration podcast. We'll be back soon.